

BYTUM SPRAY

BITUMINOUS MEMBRANE SEALANT SPRAY

DURABLE PROTECTION

The product remains flexible and seals cracks and elements by blocking water and dust infiltration.

WEATHER RESISTANCE

The special elastomer-modified bituminous formula guarantees a product that after drying resists both weathering and salt corrosion.



TECHNICAL DATA

Properties	value	USC conversion
Colour	black	-
Time required for complete drying 23 °C / 50% RH	1 - 2 h	-
Yield	4 m ²	43.06 ft ²
Application temperature	+5 / +35 °C	+41 / +95 °F
Storage temperature ⁽¹⁾	+10 / +30 °C	+50 / +86 °F

⁽¹⁾Store the product in a dry, covered location for no more than 24 months. Check the expiry date on the packaging.

Waste classification (2014/955/EU): 16 05 04.

Aerosol 1. Skin Irrit. 2. STOT SE 3. Aquatic Chronic 2.

CODES AND DIMENSIONS

CODE	content	content	
	[mL]	[US fl oz]	
BYTS	500	16.90	12



UNIVERSAL

Suitable for all types of support, it adheres to all types of shapes including roofs, gutters, terraces, skylights, PVC or metal drainpipes.

FAST INSTALLATION

The product is supplied in a convenient resealable, ready-to-use spray which can be applied without the need for additional tools.

RECOMMENDATIONS FOR INSTALLATION

SEALING OF CRACKS AND CROSSING POINTS



1 BYTUM REINFORCEMENT

FASTENING SYSTEMS WATERPROOFING

