

# PRIMER SPRAY


## UNIVERSAL SPRAY PRIMER FOR ACRYLIC ADHESIVE TAPES

### INSTANTANEOUS

Thanks to spray can application and the adjustable nozzle, no brushes or other equipment is needed for installation.

### HIGH PERFORMANCE

At a distance of approx. 30 - 50 cm from the surface approx. 6 cm of attaching area is achieved. Ideal for use with Rothoblaas tapes.



## TECHNICAL DATA

Properties	value	USC conversion
Composition	mix of thermoplastic adhesive and solvent	-
Colour	light amber	-
Time required for drying (20 °C / 50 %RH)	1-2 minutes	-
Application temperature (cartridge)	+15 / +25°C	+59 / +77 °F
Application temperature (support and ambient)	+15 / +25°C	+59 / +77 °F
Temperature resistance once dried	-10 / +100°C	+14 / +212 °F
Solvents	yes	-
French VOC classification	A+	-
VOC content	82% / 585 g/L	-
Transport temperature	+5 / +50°C	+41 / +122 °F
Storage temperature <sup>(1)</sup>	+15 / +35 °C	+59 / +95 °F
Storage time <sup>(2)</sup>	up to 12 months	-

<sup>(1)</sup>Store the product in a dry, covered location. <sup>(2)</sup>Check the expiry date on the cartridge.

Waste classification (2014/955/EU): 16 05 04.

Aerosol 1 - H222, H229.

## CODES AND DIMENSIONS

CODE	content		
	[mL]	[US fl oz]	
PRIMERSPRAY	750	25.36	12



### FAST INSTALLATION

It allows even the roughest and most fibrous surfaces to be smoothed to accommodate the application of taping or sealants.

### ADJUSTABLE

Adjustable nozzle for a more precise application adapted to each situation. Simply turn the nozzle to increase or decrease the spray area.